

# Perceptive Content Database Driver

## Installation and Configuration Guide

Version: 7.3.x

Written by: Product Knowledge, R&D  
Date: March 2020

# Copyright

Information in this document is subject to change without notice. The software described in this document is furnished only under a separate license agreement and may be used or copied only according to the terms of such agreement. It is against the law to copy the software except as specifically allowed in the license agreement. This document or accompanying materials contains certain information which is confidential information of Hyland Software, Inc. and its affiliates, and which is subject to the confidentiality provisions agreed to by you.

All data, names, and formats used in this document's examples are fictitious unless noted otherwise. Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright law, no part of this document may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Hyland Software, Inc. or one of its affiliates.

Hyland® and Hyland Software®, as well as Hyland product names, are registered and/or unregistered trademarks of Hyland Software, Inc. and its affiliates in the United States and other countries. All other trademarks, service marks, trade names and products of other companies are the property of their respective owners.

© 2020 Hyland Software, Inc. and its affiliates. All rights reserved.

## Table of Contents

<b>Copyright .....</b>	<b>2</b>
<b>Overview .....</b>	<b>4</b>
<b>Windows ODBC datasource configuration .....</b>	<b>4</b>
<b>Linux ODBC datasource configuration.....</b>	<b>4</b>
Configure Linux unixODBC Driver Manager .....	4
<i>Example: Register the database driver with unixODBC Driver Manager .....</i>	<i>5</i>
<i>Example: Create a datasource with unixODBC Driver Manager.....</i>	<i>5</i>
Configure DataDirect Driver Manager for Oracle .....	5
<b>Appendix A: ODBC database driver configuration examples .....</b>	<b>7</b>
Configure Oracle Native Driver for Windows.....	7
<b>Appendix B: ODBC database connection string properties.....</b>	<b>7</b>
Default connection properties.....	7
<i>DataDirect Oracle connection properties.....</i>	<i>7</i>
<i>Native Oracle connection properties.....</i>	<i>8</i>
<i>Native Microsoft SQL Server connection properties.....</i>	<i>8</i>
<i>Native PostgreSQL connection properties.....</i>	<i>9</i>
Override connection properties .....	9

## Overview

This document provides instructions for installing and configuring Perceptive Content Database drivers. Beginning with Perceptive Content 7.3.0, you must manually install and configure these drivers prior to the installation or upgrade of Perceptive Content. We recommend you review the supported database drivers in the Perceptive Content Technical Specifications Guide.

Each machine that directly accesses the database needs to have a manually configured database driver and ODBC datasource. You can obtain the appropriate native database driver directly from the database manufacturer. If you are running a 32-bit agent on Windows, you must install the 32-bit version of the native driver and configure a 32-bit ODBC datasource.

For more information about installing and configuring your specific version of the database driver, see the manufacturer's installation and configuration guides.

## Windows ODBC datasource configuration

To configure your Windows ODBC datasource for Perceptive Content, complete the following steps.

1. Install the appropriate database driver for your Perceptive Content database. For a list of supported database drivers, see the *Perceptive Content Technical Specifications Guide*.
2. Configure the ODBC datasources and verify connectivity to your Perceptive Content database.
 

**Note** If you are running 32-bit and 64-bit agents on the same machine, you must configure the 32-bit and 64-bit ODBC datasources with the same name.
3. If you are performing an upgrade, run the installation package for Perceptive Content agents. You will need to supply the ODBC datasource name configured in the previous step. For more information, see the appropriate Perceptive Content agent's installation and setup guide.
4. To update the ODBC datasource used by Perceptive Content update the inow.ini section with the appropriate datasource name. For more information, see the the **[ODBC] inow.ini** configuration document.

## Linux ODBC datasource configuration

### Configure Linux unixODBC Driver Manager

This section only pertains to Linux configurations that consume a native ODBC driver. You must download and install a supported version of **unixODBC** and use it to manage your installed drivers and configured datasources. For list of supported ODBC driver managers, see the Perceptive Content Technical Specifications Guide.

After you install the **unixODBC** Driver Manager you must set the **IMAGENOW\_LD\_LIBRARY\_PATH** in the **environment.ini** file in the root of Perceptive Content installation with the path to the directory containing the **libodbc.so** library.

Add the following to **environment.ini**:

```
; If present, this variable is consumed by the setenv.sh script in the Perceptive
Content bin directory.
```

```
IMAGENOW_LD_LIBRARY_PATH=/lib64
```

## Example: Register the database driver with unixODBC Driver Manager

You must register your native driver with unixODBC. The following set of steps is an example of registering an installed ODBC database driver with unixODBC. For more information, see the installation guides provided by the provider of the database driver you are installing.

1. Install the database driver package.
2. Complete the following sub-steps to create a template for your database driver.
  1. Using a text editor, open a new file.
  2. Copy and paste the following code into the file.

```
[msodbcsql_17]
Description=Microsoft ODBC Driver 17 for SQL Server
Driver=/opt/microsoft/msodbcsql17/lib64/libmsodbcsql-17.3.so.1.1
```

3. **Save** and close the text editor.
3. Run the following code to install the database driver using `odbcinst`, where `new_driver_template.txt` is the name of your new file.

```
odbcinst -i -d -f new_driver_template.txt
```

## Example: Create a datasource with unixODBC Driver Manager

The following set of steps is an example of configuring an ODBC datasource with unixODBC Driver Manager. For more information, see the installation and configuration guides provided by unixODBC.

1. Using a text editor, open a new file.
2. Copy and paste the following code into the file.

```
[inow_mssql]
Description=
Driver=msodbcsql_17
Server=<IP/hostname>
Database=INOW
```

3. **Save** and close the text editor.
4. Run the following code to install the ODBC datasource, where `new_datasource_template.txt` is the name of your new file.

```
odbcinst -i -s -l -f new_datasource_template.txt
```

## Configure DataDirect Driver Manager for Oracle

Follow these steps if you are using an Oracle Perceptive Content database on Linux. You must acquire a Datadirect package from your Perceptive Content distributor and place it on your Perceptive Content system.

1. Download and extract the Datadirect package from your Perceptive Content distributor.
 

We recommend extracting the Datadirect package to `/opt/datadirect`.
2. Complete the following sub-steps to add the `IMAGENOW_LD_LIBRARY_PATH` setting to the `environment.ini` file.
  1. Using a text editor, open the `environment.ini` configuration file. This file is located in the root of the Perceptive Content install directory.

2. Set `IMAGENOW_LD_LIBRARY_PATH` to the location of the datadirect installation's lib directory.

```
; If present, this variable is consumed by the setenv.sh script in the
Perceptive Content bin directory.
IMAGENOW_LD_LIBRARY_PATH=/opt/datadirect/lib
```

3. **Save** and close the text editor.
3. Complete the following sub-steps to create a new **odbc.ini** configuration file.

1. Using a text editor, open a new file.
2. Refer to Datadirect documentation for configuring an ODBC datasource. See example below:

```
[ODBC Data Sources]
inow_ora=DataDirect 8.0 Oracle Wire Protocol

[inow_ora]
Driver = /opt/datadirect/lib/IUora28.so
Description = DataDirect 8.0 Oracle Wire Protocol
HostName = <HostName/IP>
PortNumber = 1521
ServiceName = <ServiceName>

[ODBC]
InstallDir = /opt/datadirect
Trace = 0
TraceFile = /opt/datadirect/odctrace.out
```

3. **Save**, name the file **odbc.ini** and then close the text editor.
4. Complete the following sub-steps to add the **ODBCINI** setting to the environment.ini file.
  1. Using a text editor, open the **environment.ini** configuration file. This file is located in the root of the Perceptive Content install directory.
  2. Set **ODBCINI** to the location of the **odbc.ini** file.

```
; If present, this variable is consumed by the setenv.sh script in the
Perceptive Content bin directory.
ODBCINI=/opt/datadirect/odbc.ini
```

3. **Save** and close the text editor.
5. Complete the following sub-steps to configure the ODBC datasource in the Perceptive Content **inow.ini** configuration file.

1. Using a text editor, open the **inow.ini** configuration file.
2. Under the **ODBC** section, set the **odbc.dbms**, **odbc.dsn**, and **odbc.use.dddriver** properties. The **odbc.use.dddriver** property must be set to TRUE. Ensure that **odbc.user.id** and **odbc.user.password** properties are correctly configured for your Perceptive Content database.

```
[ODBC]
odbc.dbms=Oracle
odbc.dsn=inow_ora
odbc.user.id=inuser
odbc.user.password=
odbc.use.dddriver=TRUE
```

3. **Save** and close the text editor.

## Appendix A: ODBC database driver configuration examples

### Configure Oracle Native Driver for Windows

1. Download the 32-bit and 64-bit instantclient basic packages.
2. Download the 32-bit and 64-bit instantclient-odbc packages.
3. Extract the instantclient and instantclient-odbc packages into the same directory, keeping the 32-bit and 64-bit packages separate.
4. Once the system extracts the odbc drivers, run the following command to install the odbc drivers.

```
odbc_install.exe
```

5. After the system installs the drivers, you must configure the **TNSNAMES** file. The default location for this file is in the `ORACLE_HOME/network/admin` directory. If this directory does not exist, you can create it. This file should contain the service description for each datasources. The following is an example **tnsnames.ora** file; however, we strongly recommend you consult with your system DBA to ensure the correct configuration for your environment.

```
INOWTNS =
  (DESCRIPTION =
    (ADDRESS =
      (PROTOCOL = TCP)
      (HOST = <HostName/IP>)
      (PORT = 1521)
    )
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = INOW)
    )
  )
```

Add the 32-bit and 64-bit Oracle native driver datasources via `odbcad32`. This should use the same address name specified in the **tnsnames.ora** file.

## Appendix B: ODBC database connection string properties

Perceptive Content uses connection strings with default properties set. The following is a detailed list of properties that is set for each database configuration.

### Default connection properties

#### DataDirect Oracle connection properties

For more information about these settings, see the *Progress DataDirect for ODBC Oracle Wire Protocol Driver* manual. The provided defaults should be sufficient for most installations.

Property Name	Default Value	Configurable inow.ini ODBC Setting
DSN		odbc.dsn

UID	inuser	odbc.user.id
Password		odbc.user.password
StaticCursorLongColBuffLen	131072	odbc.max.long.varchar.column.size
IANAAppCodePage	2252	

## Native Oracle connection properties

For more information about these settings, see the "Format of the Connection String for the SQLDriverConnect Function" section in Oracle's *Using Oracle ODBC Driver* reference document.

Property Name	Default Value	Configurable inow.ini ODBC Setting
DSN		odbc.dsn
UID	inuser	odbc.user.id
PWD		odbc.user.password
FWC	F	
QTO	T	
DBA	W	
APA	T	

## Native Microsoft SQL Server connection properties

For information, see the Microsoft ConnectionString documentation.

Property Name	Default Value	Configurable inow.ini ODBC Setting
DSN		odbc.dsn
UID	inuser	odbc.user.id
PWD		odbc.user.password
APP	Current App Name	
Trusted_Connection	no	
AutoTranslate	no	
Regional	no	

## Native PostgreSQL connection properties

For more information see the PostgreSQL libpq-connect documentation.

Property Name	Default Value	Configurable inow.ini ODBC Setting
DSN		odbc.dsn
UID	inuser	odbc.user.id
PWD		odbc.user.password
Protocol	7.4-2	
UserServerSidePrepare	1	
UniqueIndex	1	
MaxVarcharSize	2048	odbc.max.char.column.size
UnknownSizes	0	
UnknownAsLongVarchar	0	
ByteaAsLongVarBinary	1	
ReadOnly	0	
BI	-5	
AB	0x0	
UserDeclareFetch	0	
LFConversion	0	

## Override connection properties

By default the aforementioned settings override any conflicting properties set on the ODBC datasource. If you need to override any of the default properties then you can remove them from the connection string by adding them to the **inow.ini ODBC** section's `odbc.connection.string.blacklist` property. This takes a comma separated list of properties to exclude from the connection string when creating an ODBC connection. We recommend you consult your system DBA before overriding any default connection string properties. Hyland Software is not responsible for consequences arising from changes to the connection string properties.

Example:

```
[ODBC]
odbc.connection.string.blacklist=UID,Password
```